



**SAFETY
JOGGER**
PROFESSIONAL



Heavy

BESTCLOG OB

Fashionable ultra-light clog for all day comfort

| | |
|---------------|---|
| Upper | Expanded EVA |
| Lining | N/A |
| Footbed | SJ foam footbed |
| Outsole | EVA/Rubber |
| Category | OB / SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.250 kg |
| Norms | EN ISO 20347:2012 |



BLK



WHT



Chemically & UV sterilizable
This shoe is chemically and UV sterilizable.



Washable 30°C
These shoes can be washed in a washing machine at 30°C.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Wet environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Expanded EVA | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | N/A | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | N/A | ≥ 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | EVA/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 96 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.35 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.35 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.21 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.22 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | N/A | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.